DATA SHEET

- · LED High Bay Light
- · Driver-on-board (DOB) system
- · Good heatsink performance
- · Epistar LED Chip, high efficiency, up to 100lm/w

Base Parameter:

Model	ALC-HB100W	ALC-HB150W	ALC-HB200W
Voltage	220-240V	220-240V	220-240V
Watt	100W	150W	200W
LED Chip	SMD2835	SMD2835	SMD2835
Lamp viewing angle	60°90°120°	60°90°120°	60°90°120°
CCT	WW/NW/CW	WW/NW/CW	WW/NW/CW
Lumen	10000LM	15000LM	20000LM
Size	D425*H335mm	D425*H345mm	D50*H48mm
Warranty	2 years	2 years	2 years

Color:

WW/NW/CW














Installation:



C Range: 0 - 360DEG C Interval: 5.0DEG Test Speed: HIGH Temperature:25.3DEG Operators:DAMIN Test Date:2018-05-28 y Range: 0 - 90DBG y Interval: 0.5DBG Test System:EVERFINE GO-2000B_VI SYSTEM V2.0.265 Rumidity:65.04 Test Distance:11.800m [K-1.0000]

Certifications:

☑ CE

☑ IP44

Applications::

- 1. Exhibition Hall
- 2. Warehouse and Factories
- 3. All types of Infrastructure
- 4. Entertainment and Sports Complex

